

AFFF Foam



Foam extinguishers are primarily designed for use on flammable liquid fires but can also be used on solid combustibles. Our Foam range includes a 6L high performance version with an improved fire rating.

Key Benefits

- 5 year warranty
- Unlike some of our competitors, we use a UK manufactured foam which includes special corrosion resistance inhibitors.
- All except 1L version have passed the 35kv electrical conductivity test
- 6L version available in standard and high performance
- 6L and 9L versions are Marine Equipment Directive Approved



Hanging Bracket



Nozzle Detail

Code	1FX	2FX	3FX	6FX	6FHPX	9FX
Capacity	1L	2L	3L	6L	6L	9L
Fire Rating	5A 21B	8A 55B	13A 70B	21A 144B	27A 183B	27A 183B
Charged Weight	2Kg	3.6Kg	5.5Kg	9.4Kg	9.4Kg	13.9Kg
Operating Pressure	12 BAR	12 BAR	12 BAR	12 BAR	12 BAR	12 BAR
Height Of Ext.	340mm	395mm	480mm	520mm	520mm	580mm
Diameter	85mm	110mm	140mm	161mm	161mm	183mm
Width Of Ext.	119mm	155mm	170mm	180mm	180mm	193mm
Discharge Time	10s	10s	14s	19s	19s	30s
Discharge Distance	4m	5m	6m	6m	6m	7m



KM 53836



0029/2018



EH11 09 01 1070
EH11 09 02 1070
EH11 09 03 1070